

## THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

**TAE-SUNG KIM** 

Serial No.: 10/766,564

Examiner:

ERDEM, FAZLI

Filed:

29 January 2004

Art Unit:

2826

For:

NOVEL CONDUCTIVE ELEMENTS FOR THIN FILM TRANSISTORS USED

IN A FLAT PANEL DISPLAY

## INFORMATION DISCLOSURE STATEMENT

Paper No. 8

Commissioner for Patents P.O.Box 1450 Alexandria, VA 22313-1450

Sir:

In accordance with 37 C.F.R. §1.56, and §§1.97 and 1.98 as amended, Applicant cites, describes and provide copies of the following art references. Under 37 C.F.R. §1.98(a)(2), a copy of U.S. patent reference(s) cited below is not attached.

- 1. U.S. Patent No. 6,448,612 to Miyazaki et al., entitled PIXEL THIN FILM TRANSISTOR AND A DRIVER CIRCUIT FOR DRIVING THE PIXEL THIN FILM TRANSISTOR, issued on September 10, 2002;
- 2. U.S. Patent No. 6,440,752 to Zhang et al., entitled ELECTRODE MATERIALS

  WITH IMPROVED HYDROGEN DEGRADATION RESISTANCE AND

  FABRICATION METHOD, issued on August 27, 2002;
- 3. U.S. Patent No. 6,348,735 to Yamaoka et al., entitled ELECTRODE FOR SEMICONDUCTOR DEVICE AND METHOD FOR MANUFACTURING SAME,

issued on February 19, 2002;

- 4. U.S. Patent No. 6,147,375 to Yamazaki et al., entitled ACTIVE MATRIX DISPLAY DEVICE, issued on November 14, 2000;
- 5. U.S. Patent No. 5,555,112 to Oritsuki et al., entitled LIQUID CRYSTAL DISPLAY DEVICE HAVING MULTILAYER GATE BUSLINE COMPOSED OF METAL OXIDE AND SEMICONDUCTOR, issued on September 10, 1996;
- 6. U.S. Patent No. 5,485,019 to Yamazaki et al., entitled SEMICONDUCTOR

  DEVICE AND METHOD FOR FORMING THE SAME, issued on January 16,
  1996;
- 7. U.S. Patent No. 5,345,108 to Kikkawa, entitled SEMICONDUCTOR DEVICE HAVING MULTI-LAYER ELECTRODE WIRING, issued on September 6, 1994;
- 8. U.S. Patent No. 5,243,202 to Mori et al., entitled THIN-FILM TRANSISTOR

  AND A LIQUID CRYSTAL MATRIX DISPLAY DEVICE USING THIN-FILM

  TRANSISTORS OF THIS TYPE, issued on September 7, 1993; and
- 9. U.S. Patent No. 4,153,529 to Little et al., entitled MEANS AND METHOD FOR INDUCING UNIFORM PARALLEL ALIGNMENT OF LIQUID CRYSTAL MATERIAL IN A LIQUID CRYSTAL CELL, issued on May 8, 1979.
- 10. U.S. Patent No. 6,147,403 to Matschitsch *et al.*, entitled *SEMICONDUCTOR BODY WITH METALLIZING ON THE BACK SIDE*, issued on November 14, 2000;

- 11. U.S. Patent No. 6,166,396 to Yamazaki, entitled SEMICONDUCTOR DEVICES, issued on December 26, 2000;
- 12. U.S. Patent No. 4,782,380 to Shankar et al., entitled MULTILAYER INTERCONNECTION FOR INTEGRATED CIRCUIT STRUCTURE HAVING TWO OR MORE CONDUCTIVE METAL LAYERS, issued on November 1, 1988;
- U.S. Patent No. 6,285,123 to Yamada et al., entitled ELECTRON EMISSION
   DEVICE WITH SPECIFIC ISLAND-LIKE REGIONS, issued on September 4,
   2001;
- 14. U.S. Patent No. 5,742,468 to Matsumoto et al., entitled ELECTRIC CHARGE GENERATOR FOR USE IN AN APPARATUS FOR PRODUCING AN ELECTROSTATIC LATENT IMAGE, issued on April 21, 1998;
- 15. U.S. Patent No. 6,271,543 to Ohtani et al., entitled ACTIVE MATRIX TYPE DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME, issued on August 7, 2001;
- 16. U.S. Patent No. 5,278,099 to Maeda, entitled *METHOD FOR MANUFACTURING A SEMICONDUCTOR DEVICE HAVING WIRING ELECTRODES*, issued on January 11, 1994;
- 17. U.S. Patent No. 5,345,108 to Kikkawa, entitled SEMICONDUCTOR DEVICE HAVING MULTI-LAYER ELECTRODE WIRING, issued on September 6, 1994;
- 18. U.S. Patent No. 6,414,738 to Fujikawa, entitled *DISPLAY*, issued on July 2, 2002;
- 19. U.S. Patent No. 6,650,017 to Akamatsu et al., entitled ELECTRICAL WIRING OF SEMICONDUCTOR DEVICE ENABLING INCREASE IN ELECTROMIGRATION (EM) LIFETIME, issued on November 18, 2003;
- 20. U.S. Patent No. 5,607,776 to Mueller et al., entitled ARTICLE FORMED BY IN-SITU CLEANING A TI TARGET IN A TI+TIN COATING PROCESS, issued on March 4, 1997;

- U.S. Patent Publication No. 2003/0222575 to Yamazaki, entitled LIGHT EMITTING APPARATUS AND METHOD OF FABRICATING THE SAME, published on December 4, 2003;
- 22. Japanese Patent Publication No. 09-153623 to Urazono, entitled *THIN FILM* SEMICONDUCTOR, published on June 10, 1997;
- 23. Japanese Patent Publication No. 09-45927 to Yamazaki, entitled SEMICONDUCTOR DEVICE, published on February 14, 1997 (corresponding to U.S. Patent No. 6,166,396 issued on December 26 2000);
- 24. Japanese Patent Publication No. 04-265757 to Kawasaki, entitled *THIN FILM*TYPE THERMAL HEAD, published on September 21, 1992;

Miyazaki et al. '612 discloses "an electronic circuit formed on an insulating substrate and having thin-film transistors (TFTs) comprising semiconductor layers." The thickness of the semiconductor layers is less than 1500 ANG., e.g., between 100 and 750 ANG. A first layer consisting mainly of titanium and nitrogen is formed on the semiconductor layer. A second layer consisting aluminum is formed on top of the first layer.

Zhang et al. '752 discloses that "an electrode for use in a ferroelectric device includes a bottom electrode; a ferroelectric layer; and a top electrode formed on the ferroelectric layer and formed of a combination of metals, including a first metal taken from the group of metals consisting of platinum and iridium, and a second metal taken from the group of metals consisting of aluminum and titanium; wherein the top electrode acts as a passivation layer and wherein the top electrode remains conductive following high temperature annealing in a

hydrogen atmosphere."

Yamaoka et al. '735 discloses that "an interlayer insulator film 11, a titanium layer 12, a titanium nitride layer 13 that serves as the barrier layer, an aluminum alloy wiring layer 15 and a protective film 18 are formed on top of the silicon substrate 10 to compose the electrode structure."

Yamazaki et al. '375 discloses in claim 2 that, "an active matrix display device according to claim 1 wherein at least one of said wiring and said gate electrode comprises a material selected from the group consisting of silicon, aluminum tantalum, titanium, tungsten, molybdenum, an alloy thereof, tantalum nitride, titanium nitride, tungsten nitride and molybdenum nitride."

Oritsuki et al. '112 discloses in claim 3 that, "a liquid crystal display substrate according to claim 1, wherein the gate electrode is made of at least one layer made of a material selected from the group consisting of aluminum tantalum and titanium and their alloys."

Yamazaki et al. '019 discloses in claim 2 that, "the device of claim 1 wherein said first wiring comprises a material selected from the group consisting of silicon, aluminum, tantalum, titanium, tungsten, molybdenum, an alloy thereof, tantalum nitride, titanium nitride, tungsten silicide, and molybdenum silicide."

Kikkawa '108 discloses" a semiconductor device having an electrode wiring which prevents generation of hillock and has good stress migration capability." A multilayer film includes at least two Al-SI-Cu alloy films and at least two titanium nitride films.

Mori et al. '202 discloses "a thin-film transistor comprises a gate electrode formed on

a glass substrate ... the gate electrode is made of titanium-containing aluminum."

Little et al. '529 discloses that "electrode surfaces are coated with a passivating material (silicon dioxide, aluminum oxide or titanium dioxide)."

Matschitsch et al. '403 discloses novel back side metallizing system which markedly reduces wafer warping of semiconductor wafers without weakening the strength of adhesion to substrate materials. On a silicon semiconductor body an aluminum layer and a diffusion barrier layer that includes titanium are provided. A titanium nitride layer is incorporated into the titanium layer because it has been demonstrated that the titanium nitride layer can compensate for a large proportion of the wafer warping that occurs. Preferably, the usual tempering for improving the ohmic contact between the aluminum layer and the silicon semiconductor body is not performed after the complete metallizing of the semiconductor body, but rather after a first, thin aluminum layer has been deposited onto the silicon semiconductor body.

Yamazaki '396 discloses that in an active matrix liquid crystal display (LCD) device, a conductor line interconnecting a drain of each thin-film transistor and a corresponding pixel electrode constructed with indium tin oxide (ITO) is formed in a three-layer structure in which an aluminum film is sandwiched between a pair of titanium films. This construction prevents poor contact and deterioration of reliability because electrical contact is established between one titanium film and semiconductor and between the other titanium film and ITO. The aluminum film has low resistance which is essential for ensuring high performance especially in large-screen LCDs.

Shankar *et al.* '380 discloses construction of a novel multilayer conductive interconnection for an integrated circuit having more than one conductive layer, comprising a lower barrier layer which may be in contact with an underlying silicon substrate, and comprising

a material selected from the class consisting of TiW and TiN; an intermediate layer of conductive metal such as an aluminum base metal; and an upper barrier layer which may be in contact with a second aluminum base metal layer and which is selected from the class consisting of TiW, TiN, MoSi.sub.x and TaSi where x equals 2 or more.

Yamada et al. '123 discloses an electron emission device which includes an electron-supply layer formed of metal or semiconductor; an insulator layer formed on the electron-supply layer; and a thin-film metal electrode formed on the insulator layer, whereby electrons are emitted when an electric field is applied between the electron-supply layer and the thin-film metal electrode. The insulator layer and the thin-film metal electrode have at least one island-like region where the thicknesses of the insulator layer and the thin-film metal electrode gradually decrease.

Matsumoto et al. '468 discloses an electric charge generator for use in an apparatus for producing an electrostatic latent image, which includes a plurality of charge generation controlling devices, each charge generation controlling device including: an insulating substrate; a line electrode formed on the insulating substrate; a solid dielectric film formed on the surface of the line electrode; a finger electrode having a hole for generating an electric charge, the hole being formed in the central part of the finger electrode, the finger electrode being formed on the solid dielectric film; a solid insulating film having a hole for passing the electric charge, the hole being formed in the central part of the solid insulating film, the solid insulating film being formed on the finger electrode; and a screen electrode having a hole for ejecting the electric charge, the hole being formed in the central part of the screen electrode, the screen electrode being formed on the surface of the finger electrode via the solid insulating film; wherein the plurality of charge generation controlling devices are arranged on the insulating substrate so as to form the electric charge generator. The solid insulating film is formed of a multilayer solid insulating film including a surface-side layer made of an inorganic insulating film and a

substrate-side layer made of an organic insulating film whereby the durability and the reliability are improved.

Ohtani et al. '543 discloses an active matrix type display device having a sufficient auxiliary capacitance and a high aperture ratio. In the device, an auxiliary capacitance (a black mask being in contact with an inorganic layer/the inorganic layer/a pixel electrode being in contact with the inorganic layer) is formed on an interlayer insulating film made of an organic resin film.

Maeda '099 discloses a semiconductor device having a p+ -type silicon source region, an insulating film formed on the source region and having a contact hole, and a wiring electrode connected to the source region through the contact hole. The wiring electrode has a Ti layer formed on the insulating film and an exposed surface of the source region, a TiN layer formed on the Ti layer, and an Al layer formed on the TiN layer.

Kikkawa '108 discloses a semiconductor device having an electrode wiring which prevents generation of hillock and has good stress migration capability. A multi layer film including at least two Al-Si-Cu alloy films and at least two titanium nitride films formed by reactive sputtering laminated alternately with the Al-Si-Cu alloy films has a high mechanical strength against deformation and can effectively prevent generation of hillock. Ti-Al intermetallic compounds are formed in grain boundaries and in interfaces, which is effective to restrict generation of a void. Propagation of a void can be prevented by the intermediate titanium nitride film. Further, the formation of the Ti-Al compounds is restricted and an increase of resistance is negligible.

Fujikawa '738 discloses that, in a display device such as a liquid crystal display device, in order to connect electrodes and wiring with a low resistance, the first titanium nitride film

14 having a hexagonal crystal structure for preventing silicon diffusion is intervened between the drain region 5 composed of a polycrystalline silicon film and the drain electrode 9 composed of an aluminum film. The second titanium nitride film 15 having a hexagonal crystal structure which can be deposited by sputtering with the same target as that for the titanium film 13 and the first titanium film 14 is intervened between the transparent display electrode 12 composed of an ITO film and the drain electrode 9 composed of an aluminum film in order to bring them into ohmic contact. Since the second titanium nitride film 15 is resistant to an etchant for the silicon oxide film and to an etchant for the ITO film, the drain electrode 9 is protected when etching is performed.

Akamatsu et al. '017 discloses a method for manufacturing a semiconductor device having on a silicon substrate semiconductor elements and aluminum (Al) alloy wiring leads as electrically connected thereto. The method includes the steps of forming on the silicon substrate an Al alloy layer containing therein copper (Cu), and forming on the Al alloy layer a titanium nitride (TiN) film with enhanced chemical reactivity by using sputtering techniques while applying thereto a DC power of 5.5 W/cm.sup.2 or less. Fabrication of such reactivity-rich TiN film on the Al alloy layer results in a reaction layer of Al and Ti being subdivided into several spaced-apart segments. In this case, the reaction layer hardly serves as any diffusion path; thus, it becomes possible to prevent Cu as contained in the Al alloy layer from attempting to outdiffuse with the reaction layer being as its diffusion path. This makes it possible to suppress or minimize unwanted fabrication of AlN on or above the surface of an Al containing lead pattern, thereby enabling increase in electromigration (EM) lifetime of electrical interconnect leads used.

Mueller et al. '776 discloses a novel method of in-situ cleaning a Ti target in a Ti+TiN anti-reflective coating process when such Ti and TiN deposition process are conducted in the same process chamber by the addition of a simple process step and without the use of a shutter.

Yamazaki et al. '575 discloses that although an ink jet method known as a method of selectively forming a film of a high molecular species organic compound, can coat to divide an organic compound for emitting three kinds (R, G, B) of light in one step, film forming accuracy is poor, it is difficult to control the method and therefore, uniformity is not achieved and the constitution is liable to disperse. In contrast thereto, according to the invention, a film comprising a high molecular species material is formed over an entire face of a lower electrode connected to a thin film transistor by a coating method and thereafter, the film comprising the high molecular species material is etched by etching by plasma to thereby enable to selectively form a high molecular species material layer. Further, the organic compound layer is constituted by a material for carrying out luminescence of white color or luminescence of single color and combined with a color changing layer or a coloring layer to thereby realize full color formation.

Urazono '623 aims at enabling prevention of voids and hillocks and hence prevention of disconnection without increasing wiring resistance, by providing a multilayer structure of wiring in which an aluminum metal film and a refractory metal film are stacked. English language Abstract is attached.

Yamazaki '927 aims at eliminating contact failures and solve the reliability problems for an active matrix liquid crystal display. English language Abstract is attached.

Kawasaki '757 relates to a thin film type thermal head having high reliability by preventing breaking of wire caused by energizing a power feed layer. English language Abstract is attached.

The citation of the foregoing references is not intended to constitute an assertion that other or more relevant art does not exist. Accordingly, the Examiner is requested to make a

PATENT P57001

wide-ranging and thorough search of the relevant art.

A fee of \$180.00 is incurred by filing of the Information Disclosure Statement. Applicant's check drawn to the order of Commissioner accompanies this Amendment. Should the check become lost, be deficient in payment, or should other fees be incurred, the Commissioner is authorized to charge Deposit Account No. 02-4943 of Applicant's undersigned attorney in the amount of such fees.

Respectfully submitted,

Robert E. Bushnell

Reg. No.: 27,774

1522 "K" Street, N.W., Suite 300 Washington, D.C. 20005

Area Code: (202) 408-9040

Folio: P57001 Date: 7/12/05 I.D.: REB/kf

SERIAL NUMBER 10/766,564 DOCKET NO. INFORMATION DISCLOSURE STATEMENT P57001 PTO-1449 (PAGE 1 OF 2) APPLICANT TAE-SUNG KIM FILING DATE 29 January 2004 GROUP 2826 U.S. PATENT DOCUMENTS SUBCLASS EXAMINER DATE NAME CLASS **DOCUMENT NUMBER FILING DATE** 9/02 6,448,612 Miyazaki et al. 6,440,752 8/02 Zhang et al. 2/02 6,348,735 Yamaoka et al. 6,147,375 11/00 Yamazaki et al. 5,555,112 9/96 Oritsuki et al. Yamazaki et al. 5,485,019 1/96 5,345,108 9/94 Kikkawa 5,243,202 9/93 Mori et al. 4,153,529 5/79 Little et al. 6,147,403 11/00 Matschitsch et al. 6,166,396 12/00 Yamazaki 4,782,380 11/88 Shankar et al. 9/01 6,285,123 Yamada et al. 5,742,468 4/98 Matsumoto et al. TRANSLATION FOREIGN PATENT DOCUMENTS **DOCUMENT NUMBER** SUBCLASS YES NO **CLASS** DATE COUNTRY

## DOCUMENT NUMBER DATE COUNTRY CLASS SUBCLASS YES NO JP09-153623 6/97 Japan Abstract Abstract JP09-45927 2/97 Japan Abstract Abstract JP04-265757 9/92 Japan Abstract Abstract

OTHER DOCUMENTS (Including Author, Title, Date, Pertinent Pages, etc.)

**EXAMINER:** 

DATE CONSIDERED:

EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP §609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

OTPIR	PTO-1449 (PAGE	URE STAT	EMENT	SERIAL NUMBER 10/766	5,564	DOCKET NO. P57001							
a 7		E 2 OF 2)		APPLICANT									
inr Ju				FILING DATE 29 Januar	GROUP 2826								
CARADE	TAR SEC.		U.S. PATER	NT DOCUMENTS									
EXAMMER	DOCUMENT NUMBER		NAME	CLASS	SUBCLASS	FILING DATE							
	6,271,543	8/01	Ohtani et al.										
	5,278,099	1/94	Maedda										
	5,345,108	9/94	Kikkawa	<del></del> · · · · · · · · · · · · · · · · · ·									
	6,414,738	7/02	Fujikawa										
	6,650,017	11/03	Akamatsu										
	5,607,776	03/97	Mueller et al.										
	2003/0222575	12/03	Yamazaki										
		FOREIGN	PATENT DOC	UMENTS			TRANS	LATION					
DOCUMENT NUMBER DATE			С	OUNTRY	CLASS	SUBCLASS	YES	NO					
	OTHER DO	CUMENT	S (Including A	uthor, Title, Date, P	ertinent Pa	ages, etc.)							
EXAMINE	<u> </u> :R:		DATE CONSID	DATE CONSIDERED:									

EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP §609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

Thus #

Approved for use through 9/30/2000. OMB 9651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL APP						Complete If Known										
					Appli	Application Number				10/766564						
Pation yees are subject to annual revision.						ing Date				29 January 2004						
First Exam						irst Named Inventor			十	Tae-Sung KIM						
						xaminer Name			$\dashv$	Fazli ERDEM						
HAUE							/Art Unit 2826						(			
TOTAL AMOUNT OF PAYMENT (\$) 180.00 Attor						ney D	y Docket No. P57001									
METHOD OF PAYMENT (check one)						-	F			FEE CALCULATION						
1. ■ Payment Enclosed: (CHECK #49346)						Fee Code	Fee (\$)	Fee Code			Fee Descript	ion		Feè Paid		
■ Obesity D. Orestii Orest D. M. J. C. J. C. C.										MISCELLANEOUS						
■ Check □ Credit Card □ Money Order □ Other				1801	\$790	2801	\$395	Request for continued examination (RCE)				\$				
Charge Any Additional Fee Required Under 37 C.F.R. §1.16 and 1.17.						1806	\$180			Submission of an IDS				\$180.00		
	C Applicant deline and the state of the stat						1814	\$130 \$40	2814	\$65	-	Statutory disclaimer			\$ \$	
Applicant claims small entity status. See 37 CFR 1.27						8021	\$40			Recordation of assignment per property \$  TRADEMARK						
2. The Commissioner is hereby authorized to charge any deficiency and credit any over payments to:						6001/	7001		\$335					\$		
	Depo	sit Ac	count	Numbe	er: <b>02-49</b> 4	3		6002/	7002		\$100	\$100 Amendment to Allege Use, per class				\$
					CULATION			6003/	7003		\$100	00 Statement of Use, per class				\$
	Fee	Fee	Fee				Fee	6004/	7004		\$150	Request for six-	month extension	on of tim	ne, per class	\$
Code	(\$) Code (\$)			Fee Description		Paid	6205/	7205		\$100	§8 affidavit, per	class			\$	
			EX.	TENSION	OF TIME FEES			6208/	7208		\$200	§15 affidavit, pe	er class			\$
1251	120	2251	60	Extensio	n for reply within first	eply within first month \$			7201		\$400	.,				\$
1252	450	2252	225	Extensio	n for reply within sec	ond month	\$.	6403/	7403		\$100	00 Ex parte appeal, per class				\$
1253	1020	2253	510	Extensio	n for reply within third	month	\$	ł				PETITION				
1254	1590	2254	795	Extensio	on for reply within fourth month \$		1462			\$400	Petitions to Dire	Petitions to Director (Group I)			\$	
1265	2160	2255	1080	Extensio	on for reply within fifth month \$		1463			\$200		Petitions to Director (Group II)			\$	
•					PPEAL		1464			\$130		Petitions to Director (Group III)			\$	
1401	500	2401	250	Notice of			\$	1452	\$500	2452	\$250	Petitions to application	etitions to revive unavoidably abandone pplication			\$
1402	500	2402	250	-	a brief in support of an appeal \$			1453	\$1500	2453	\$750	Petitions to re application	abandoned	\$		
1403	1000	2 2403 500 Request for oral hearing			\$					PATENT MAINTEN				_		
4004	000	0001	400		AIMS		_		\$900	2551		•				\$
1201 1202	200	2201			dent claims in excess		\$					Due at 7.5 years			\$	
		2202			excess of 20 (4)		\$					Due at 11.5 yea				\$
Other Fee (specify)\$														\$		
Other Fee (specify)\$							Other Fee (specify) \$						\$			
Other Fee (specify) \$					Other	Fee (spe	cify)		. ,		<del>- 1</del>		\$			
SUBTOTAL: LEFT COLUMN \$.00									SI	UBTOTAL: RIC	GHT COLU	MN	\$180.00			
SUBMITTED BY										1	Complete (if applicable)					
Typed or Printed Name  Robert E. Bushnell, Es					sq.			Re	eg. Number		27.	774				
Signature Rose Date						12 July	2005		Deposit Acco	unt						